

The AirCheck™-White List 2024

Fan Types for Highly Efficient and Resource Friendly Crop Protection in 3D-Crops

Copyright© MABO 2018 - 2024
Constituted on February 26, 2024

Fan Type	Maximum working height at 3,0 m row distance m	Maximum angle of the air flow Degree	Usable air flow $m^3_{eff} h^{-1}$	Usable air flow per metre maximum working height $m^3_{eff} h^{-1} m^{-1}$	Power consumption at PTO kW	Diesel consumption at fuel tank $l h^{-1}$	CO ₂ -emissions $kg h^{-1}$	Energy efficiency Diesel consumption per m ³ usable air flow per hour $ml m^{-3}_{eff} h^{-1}$	Noise emission dB (A)	Drift reduction classification (JKI)* %	AirCheck®-air distribution quality: Classification
Zupan DT-V	2,4	26	45.120	18.800	7,70	2,59	6,87	0,057	84	75	Air Distribution
Weber QU15 H	2,5	-1	31.181	12.472	5,35	1,80	4,77	0,058	79	90 / 75*	Low Loss Spray Application
Lochmann 80UQW 2	2,6	17	51.013	19.620	10,96	3,69	9,78	0,072	84	75	Air Distribution
Weber QU16 H	2,8	5	38.256	13.663	7,73	2,60	6,90	0,068	78	90	Low Loss Spray Application
Wanner ZA28	2,8	39	41.341	14.765	3,12	1,05	2,78	0,025	83	90	Low Loss Spray Application
Lochmann 80UQ2-A	3,3	-2	50.320	15.248	12,70	4,28	11,33	0,085	87	90	Air Distribution
Weber QU17 H	3,3	5	43.376	13.144	7,73	2,60	6,90	0,060	79	50	Low Loss Spray Application
Weber QU15,5-12 H	3,3	21	47.011	14.246	9,26	3,12	8,26	0,066	79	75	Low Loss Spray Application
Zupan DT CR-O	3,4	43	53.009	15.591	19,20	6,46	17,13	0,122	87	75	Air Distribution
Wanner H63	3,5	15	41.221	11.777	7,01	2,36	6,26	0,057	83	95	Low Loss Spray Application
Lochmann 90UQH2-A	3,5	41	68.904	19.687	16,70	5,62	14,90	0,082	90	95 / 75**	Low Loss Spray Application
Waibl Q / 09	3,5	45	61.482	17.566	11,00	3,70	9,81	0,060	87	75	Air Distribution
Wanner ZA32	3,5	49	59.197	16.913	8,56	2,88	7,64	0,049	84	90 / 75*	Low Loss Spray Application
Zupan DT MAXI-O	3,6	49	72.737	20.205	18,10	6,09	16,15	0,084	85	75	Air Distribution
Zupan DT-O	3,7	49	56.205	15.191	8,70	2,93	2,33	0,052	80	95 (AFC) / 75**	Low Loss Spray Application
Wanner 36GA nA	3,7	52	74.800	20.216	11,75	3,96	10,48	0,053	84	90	Low Loss Spray Application
Lochmann 80UQ 2	3,8	50	60.820	16.005	11,10	3,74	9,90	0,061	85	75	Air Distribution
Lochmann 90Q 2	3,9	55	69.774	17.891	17,30	5,82	15,44	0,083	86	90	Low Loss Spray Application
Lochmann 90UQ 2	3,9	56	81.449	20.884	17,30	5,82	15,44	0,072	86	75	Air Distribution
Wanner 36GA mhA	4,0	53	69.455	17.364	11,75	3,96	10,48	0,057	84	75	Air Distribution
Wanner 42GA	4,0	55	107.871	26.968	16,65	5,61	14,86	0,052	89	95	Low Loss Spray Application
Lochmann 90QB 2	4,0	59	75.184	18.796	19,60	6,60	17,49	0,088	87	75	Air Distribution
Lochmann 90UQH 2	4,1	53	74.521	18.176	16,40	5,52	14,63	0,074	87	75	Air Distribution

Please note that the listing of a fan type in the **AirCheck®**-white list only confirms the basic suitability of this fan **type** for target adapted spray application. This does not automatically apply to any individual fan from the series due to unavoidable deviations of production and assembly of air ducting components and the necessity to adjust the air distribution for canopy adapted spray application to the requirements of the buyer through an individual adjustment and verification. This suitability is only confirmed by the positive air distribution protocol of the individual fan according to the actual **AirCheck®**-guidelines, the entering of the individual number of an **AirCheck®**-test badge in this protocol, and the affixing of this test badge on the sprayer.

* Recognised spray drift reduction only with nozzles listed in the assortment for fruit growing (OFD75, OIFD75-1 and OIFD75-2) as well as for grape vines (WIFD50-1 WIFD75-3, WIFD90-4 and WIFD75-2) and fan specific provisions (z. B. switching off air support in the first 3 or 5 tree rows in direction of a surface water, reduction of fan speed e.g. left/right and a reduction of liquid pressure) depending on the spray drift reduction class of the fan used and the corresponding buffer zone of the individual product. Details see at "Verzeichnis verlustmindernde Geräte" of the JKI at Braunschweig, Germany.

** Dosing according JKI specification

AFC = Air flow control

- Fans sorted by maximum working height, maximum vertical angle of the airstream and manufacturer.

- All figures based on testing PTO speed 460 min⁻¹ at high fan gear and a measuring distance of 1,5 m, corresponding to a row distance of 3,0 m. For a group of orchards that is going to be treated with the desired fan type, adjustment will be done indirectly to the orchard block requiring the highest vertical angle of the air flow.

- Figures related to power consumption are recorded at the drive unit, figures related to Diesel consumption from the fuel tank are calculated from these values with an energy efficiency of the tractor of 30%.